

24" Marvel Professional High-Efficiency Dual Zone Wine Refrigerator

Model # MP24WD

Performance

- Dynamic Cooling Technology™ delivers the industry's best temperature stability and rapid cool down, safely bringing wine to temperature without compromising integrity
- Two independently monitored zones store your wine collection at separate temperatures
- Vibration Neutralization System[™] protects wine from agitation, allowing it to come to full maturation
- Thermal-efficient cabinet ensures optimum preservation and energy efficiency while maximizing capacity
- Argon-filled, UV-resistant tinted dual pane glass door protects contents from damaging ultraviolet light, while conserving energy
- Now even quieter operation thanks to exclusive design enhancements to buffer and minimize sound

Storage Capabilities

- 4.9 cu. ft. capacity, stores 40 bottles of wine total
 - Upper zone includes (3) 8-bottle smooth-glide full wine racks
 - Lower zone includes (1) 8-bottle smooth-glide full wine rack and (2)
 4-bottle smooth-glide half-depth wine racks
- Heavy-gauge wire wine racks are shaped to safely cradle each wine bottle
- Full-extension Smooth Glide[™] ball bearing shelf system prevents jarring

Touchpad Controls

- Multifunction Marvel Intuit™ Integrated Controls allow you to select a precise cabinet temperature from 45° F to 55° F in the lower zone and 55° F to 62° F in the upper zone
- Vacation mode conserves energy during times when unit is not in use

Aesthetics

- Soft-close integrated hinge provides a seamless zero clearance installation and a smooth gentle close
- At the touch of a button, change the interior light color to sapphire blue, amber glow, or arctic white
- Two-stage theater-style lighting offers full or half illumination
- Elegant midnight black interior
- Professional styling: stainless-steel-framed glass door, sturdy fulllength handle, sleek stainless steel shelf fronts and stainless steel toe kick adjustable to 4" with leveling legs
- Finish options: stainless steel or overlay (panel ready)

Additional Convenience

- Close Door Assist System[™] gently and automatically draws door to a close, ensuring door is never accidentally left ajar
- Door lock provides added safety and security
- 3-year parts and labor warranty, 5-year sealed system parts warranty



Ordering Options

Stainless Frame, Glass Door with Lock, Integrated Right Hinge, Professional Handle	MP24WDG5RS
Stainless Frame, Glass Door with Lock, Integrated Left Hinge, Professional Handle	MP24WDG5LS
Panel-Ready Framed Glass Door with Lock, Integrate Right Hinge (Handle Not Included)*	ed MP24WDF5RP
Panel-Ready Framed Glass Door with Lock, Integrate Left Hinge (Handle Not Included)*	ed MP24WDF5LP

*Easy installation! No panel kit required. Consult your cabinet maker for overlay panel and handle options.




Finish Options






Stainless Steel Solid Overlay (Panel Ready)*



Panel Overlay Dimensions



Rough-In Dimensions

A. Rough-In Width	24"
B. Rough-In Height	34 1/4" to 35 1/25"
C. Rough-In Depth	24"

Product Dimensions

D. Width	23 7/8"	
E. Height	34" to 35"	
F. Depth	21 1/2"	
G. Depth to Front of Door	Solid Door	23 23/32"
	Overlay Door	22 7/8" Without Handle
H. Depth to Handle	26 7/32" (Stainless Steel)	
I. Depth with door at 90°	Solid Door	46 13/32"
	Overlay Door	46 1/2"

Product Features

Floductieatures		
Interior Cabinet Finish	Black	
Capacity	Up to 40 wine bottles: 24 Upper Zone / 16 Lower Zone	
Shelving System	Smooth Glide System™	
Shelf Fronts	Stainless Steel	
Other Storage	6 Wine Racks	
Interior Lighting	Tri-Color LED	
Toe Grill Finish	Stainless Steel	
Hinge	Soft Close Integrated Hinge	
Handle	Professional (Panel Overlay Does Not Include Handle)	
Control Type	Intuit™	
Temperature Range	Top: 55° to 62° F Bottom: 45° to 55° F	
Lock	Yes	
Electrical Requirements	120V / 60Hz / 15A	
Length of Power Cord	6′	
Shipping Weight	160 lbs	
Finishes	Stainless Steel, Overlay	
Vacation Mode	Yes	
Agency Approvals	CSA	
Temperature Range Lock Electrical Requirements Length of Power Cord Shipping Weight Finishes Vacation Mode	Intuit™ Top: 55° to 62° F Bottom: 45° to 55° F Yes 120V / 60Hz / 15A 6′ 160 lbs Stainless Steel, Overlay	

For comprehensive installation instructions, please visit www.marvelrefrigeration.com to access the owner's guide.