SUBMITTAL DATA: DUCTLESS MINI SPLIT A/C



UL

JOB NAME:	LOCATIO	ON:		
PURCHASER:				
ENGINEER:				
SUBMITTED TO:	FOR:	REFERENCE	APPROVAL	CONSTRUCTION
SPECIFICATIONS	TAS-12U			
SEER	13			
EER	12.1			
HSPF	n/a			
Voltage	115V/60HZ/1PHASE			
Breaker Size (A)	20			
RLA Cool/Heat (A)	8.8/9.0			
NEA COOI, FICUT (A)			0.0/ 5.0	
Indoor Unit				
Airlow Hi Speed (CFM)	400			
Noise Level Hi Speed (Db)	42			
Width (Inches)	35.25			
Depth (Inches)	7.89			
Height (Inches)	11.2			
Unit Weight (lbs)	27			
<u> </u>				
Outdoor Unit				
Noise Level (dB)	55			
Width (Inches)	33.5			
Depth (Inches)	11.4			
Height (Inches)	24			
Unit Weight (lbs)	115			
Line Sets				
Refrigerant	R410A			
Pipe Size	1/4", 1/2"			
Maximum Length	49			
Maximum Vertical	21			
Factory Charge for (Ft)	25			
Additional Charge (Oz/Ft)	0.3			
Controls				
Control Method	Wireless Remote Control			
Communication Control Voltage	115V			

Safety

^{*}All specification subject to change without notice.