

CAPACITORS

SINGLE PURPOSE RUN CAPACITORS

370 Volt Models Metal

- * Internal construction: Self-healing metallized polypropylene film Dielectric Fluid: Eccol II. IIIB liquid NFPA Classification.
- * Flashpoint: 430°F (221°C); Fire point: 495°F (257°C).
- * Cover Material: Tin Plate Steel.
- * Case Material: Tin Plate Steel; or Aluminum.
- * Interrupter: Pressure sensitive, UL recognized. Rated for 10,000 AFC..
- * Terminals: Multiple blades (3 or 4), tinned steel quick connect 0.25 in (6.35 mm) X 0.032 in (0.813 mm).
- * Capacitor Tolerance: ±6% Std. ±3% and ±10% available.
- * Operating Temperature: -40°F (-40°C) to 158°F (70°C)
- * AC Voltage Ratings: 240, 300, 330, 370, 440, and 660 VAC.
- * UL and or CSA approved.



Volts AC	Configuration	MFD	Width	Depth	Height	PARTNERS CHOICE Part Number
370	OVAL	4	1 5/16"	2 5/32"	2 5/8"	01-0000
370	OVAL	5	1 1/4"	2"	1 1/2"	01-0001
370	OVAL	6	1 5/16"	2 5/32"	2 5/8"	01-0002
370	OVAL	7.5	1 5/16"	2 5/32"	2 5/8"	01-0003
370	OVAL	10	1 5/16"	2 5/32"	2 5/8"	01-0004
370	OVAL	12.5	1 5/16"	2 5/32"	3"	01-0005
370	OVAL	15	1 5/16"	2 5/32"	3 3/4"	01-0006
370	OVAL	17.5	1 29/32"	2 29/32"	2 5/8"	01-0211
370	OVAL	20	1 29/32"	2 29/32"	3"	01-0007
370	OVAL	25	1 29/32"	2 29/32"	4 3/4"	01-0008
370	OVAL	30	1 29/32"	2 29/32"	4 3/4"	01-0009
370	OVAL	35	1 29/32"	2 29/32"	4 3/4"	01-0010
370	OVAL	40	1 29/32"	2 29/32"	4 3/4"	01-0011
370	OVAL	45	1 29/32"	2 29/32"	4 3/4"	01-0012
370	OVAL	50	1 29/32"	2 29/32"	4 3/4"	01-0013
370	OVAL	55	1 29/32"	2 29/32"	4 3/4"	01-0014
370	OVAL	60	1 29/32"	2 29/32"	4 3/4"	01-0015
370	OVAL	65	1 29/32"	2 29/32"	4 3/4"	01-0016
370	OVAL	70	1 29/32"	2 29/32"	4 3/4"	01-0017
370	OVAL	75	1 29/32"	2 29/32"	4 3/4"	01-0018
370	OVAL	80	1 29/32"	2 29/32"	4 3/4"	01-0019
370	ROUND	4			2 5/8"	01-0020
370	ROUND	5			2 5/8"	01-0021
370	ROUND	6			2 5/8"	01-0022
370	ROUND	7.5			2 5/8"	01-0023
370	ROUND	10			2 5/8"	01-0024
370	ROUND	12.5			2 5/8"	01-0025
370	ROUND	15			2 5/8"	01-0026
370	ROUND	17.5			2 5/8"	01-0212
370	ROUND	20			2 5/8"	01-0027
370	ROUND	25			3"	01-0028
370	ROUND	30			3"	01-0029
370	ROUND	35			3 3/4"	01-0030
370	ROUND	40			3 3/4"	01-0031
370	ROUND	45			3 3/4"	01-0032
370	ROUND	50			3 3/4"	01-0033
370	ROUND	55			3 3/4"	01-0034
370	ROUND	60			4 3/4"	01-0035

CAPACITORS

SINGLE PURPOSE RUN CAPACITORS

370 Volt Models Metal

Volts AC	Configuration	MFD	Height	PARTNERS CHOICE Part Number
370	ROUND	65	4 3/4"	01-0036
370	ROUND	70	4 3/4"	01-0037
370	ROUND	75	4 3/4"	01-0038
370	ROUND	80	4 3/4"	01-0039

440 Volt Models Metal

- * Internal construction: Self-healing metallized polypropylene film
- * Dielectric Fluid: Eccol II. IIIB liquid NFPA Classification.
- * Flashpoint: 430°F (221°C); Fire point: 495°F (257°C).
- * Cover Material: Tin Plate Steel.
- * Case Material: Tin Plate Steel; or Aluminum.
- * Interrupter: Pressure sensitive, UL recognized. Rated for 10,000 AFC.
- * Terminals: Multiple blades (3 or 4), tinned steel quick connect 0.25 in (6.35 mm) X 0.032 in (0.813 mm).
- * Capacitor Tolerance: ±6% Std. ±3% and ±10% available.
- * Operating Temperature: -40°F (-40°C) to 158°F (70°C).
- * AC Voltage Ratings: 240, 300, 330, 370, 440, and 660 VAC.
- * UL and or CSA approved.



Volts AC	Configuration	MFD	Width	Depth	PARTNERS CHOICE Part Number
440	OVAL	4	1 5/16"	2 5/32"	01-0040
440	OVAL	5	1 5/16"	2 5/32"	01-0041
440	OVAL	6	1 5/16"	2 5/32"	01-0042
440	OVAL	7.5	1 5/16"	2 5/32"	01-0043
440	OVAL	10	1 5/16"	2 5/32"	01-0044
440	OVAL	12.5	1 29/32"	2 29/32"	01-0045
440	OVAL	15	1 29/32"	2 29/32"	01-0046
440	OVAL	20	1 29/32"	2 29/32"	01-0047
440	OVAL	25	1 29/32"	2 29/32"	01-0048
440	OVAL	30	1 29/32"	2 29/32"	01-0049
440	OVAL	35	1 29/32"	2 29/32"	01-0050
440	OVAL	40	1 29/32"	2 29/32"	01-0051
440	OVAL	45	1 29/32"	2 29/32"	01-0052
440	OVAL	50	1 29/32"	2 29/32"	01-0053
440	OVAL	55	1 29/32"	2 29/32"	01-0054
440	OVAL	60	1 31/32"	2 21/32"	01-0055
440	OVAL	65	1 31/32"	2 21/32"	01-0056
440	OVAL	70	1 31/32"	2 21/32"	01-0057
440	OVAL	75	1 31/32"	2 21/32"	01-0058
440	OVAL	80	1 31/32"	2 21/32"	01-0059
440	ROUND	4	1 3/4"	2 5/8"	01-0060
440	ROUND	5	1 3/4"	2 5/8"	01-0061
440	ROUND	6	1 3/4"	2 5/8"	01-0062
440	ROUND	7.5	1 3/4"	2 5/8"	01-0063
440	ROUND	10	1 3/4"	2 5/8"	01-0064
440	ROUND	12.5	1 3/4"	2 5/8"	01-0065