

CONTACTORS

DEFINITE PURPOSE CONTACTORS

1, 2 AND 3 POLE



Vendor Part Number	No. Poles	FLA			LRA			Res. Rating				Coil Volts	Subs To	PARTNERS CHOICE Part Number
		240V	480V	600V	240V	480V	600V	240V	277V	480V	600V			
3100A-15Q1	1	25	25	25	150	50	40	30	30	30	30	24	01-0109	621661
3100-10Q1	1	25	25	25	150	50	40	30	30	30	30	24	01-0109	621957
3100A-15Q14	1	35	31	31	180	75	50	40	40	40	40	24	None	621662
3100A-15Q19	1	40	40	40	240	200	160	50	50	50	-	24	01-0115	621665
3100-20Q3	2	20	20	20	120	100	80	30	30	30	30	24	None	621668
3100-20Q5	2	25	25	25	150	125	100	35	35	35	35	24	None	621958
90-244	2	30	21	17	150	125	100	35	40	40	40	24	01-0118	620423
90-247	2	40	-	-	240	-	-	-	-	-	-	24	01-0121	*621651
3100-30Q9	3	30	30	30	180	150	120	40	40	40		24	None	621667
3100-30Q9SB	3	30	30	30	180	150	120	40	40	40	40	24	01-0124	**621832
90-170	3	40	-	-	-	-	-	-	-	-	-	24	01-0127	620734
3100Y-30117	3	60	60	60	360	360	240	75	75	75	75	24	01-0133	621838

* Includes Box Lugs L1/L2/T1/T2

** Auxiliary switch included

UNIVERSAL DEFINITE PURPOSE CONTACTORS

1 AND 2 POLE

* Contact block and carrier are high quality electrical-grade thermosetting resin.

* Temperature Range: -40°F to 150°F.

* Conforms to UL and ARI specifications.

* Coil Frequency: 50/60 hertz.

* Class B (130°C) Coil Insulation.

* Pressure connectors and Double 1/4" Quick Connects.

* Operates at 85% of nominal coil voltage; 110% maximum.

* Continuous duty cycle.



Poles	Amp	Coil VAC	Res DC Ohms	Current MA	Nom VA	Max Inrush VA	PARTNERS CHOICE Part Number
1	20	24	18	20.8	5	28	01-0106
1	20	120	420	41.6	5	28	01-0107
1	20	240	1800	20.8	5	28	01-0108
1	25	24	18	20.8	5	28	01-0109
1	25	120	420	41.6	5	28	01-0110
1	25	240	1800	20.8	5	28	01-0111
1	30	24	18	20.8	5	28	01-0112
1	30	120	420	41.6	5	28	01-0113
1	30	240	1800	20.8	5	28	01-0114
1	40	24	18	20.8	5	28	01-0115
1	40	120	420	41.6	5	28	01-0116
1	40	240	1800	20.8	5	28	01-0117
2	30	24	11	270.8	6.5	30	01-0118
2	30	120	237	54.16	6.5	30	01-0119
2	30	240	1000	27.08	6.5	30	01-0120
2	40	24	11	270.8	6.5	30	01-0121
2	40	120	237	54.16	6.5	30	01-0122
2	40	240	1000	27.08	6.5	30	01-0123