# AF/AFG oil Burner



# **Product Sheet**

# **Description**

Beckett models AF and AFG burners utilize technically advanced components to meet increased demand for improved burner performance and reliability in modern, high-efficiency appliances. These performance-enhancing features will help you meet today's toughest heating system challenges.



# **Advanced Components**



#### **Beckett GeniSys Burner Control**

- Programmable pre/post-time settings.
- Three status lights for system monitoring & diagnostics.
- Limited reset and limited recycle.
- Technician Pump Prime mode.



#### Beckett Igniter

- Electrodes last approx. 50% longer.
- Higher output voltage for reliable ignition.
- Approximately 75% lower input amps.



#### CleanCut Pump

- Integrated solenoid valve.
- Higher capacity design delivers up to 3 GPH at 100psi on the AFG burner.
- The CleanCut has fewer moving parts and reduces motor load.



#### **PSC Motor**

- Lower amp draw & cooler operation.
- Delivers more power with the PSC design (permanent split capacitor).
- Proven durability after 10 years of high reliability in the field.
- Ball bearings for longer life.

The AF and AFG burners have been supplied on original equipment boilers, furnaces, and water heaters for many years. As technology improved, so have our burners and components. If a burner is more than 10 years old, a new AF/AFG chassis is a simple way to upgrade the sytem. Installation by your service company is uncomplicated and a new burner comes with a 5-year factory warranty.

Beckett, the trusted name in oil heat since 1937.

# AF/AFG oil Burner



# **Product Sheet**

## **Specifications**

## Capacity

- 0.40 - 3.00 GPH

56,000 - 420,000
btu/hr input

#### **Fuels**

 No.1 or No.2 heating oil (ASTM D396) only

#### Fuel Unit

Single-stage or two-stage

## Electrical Characteristics

Motor: 1/7 HP, PSC,

NEMA 48M frame

Power 120V AC, 60 Hz,

Supply: single phase Ignition: Continuous duty

solid-state igniter

Operating 5.8 Amps Max. Load:

# Dimensions (standard)

Height: 11-1/2"Width: 12-7/8"

Depth: 6-9/16" (chassis

only)

# Dimensions (with cover)

Height: 12-1/2" Width: 15" Depth: 9-1/4"

Airtube Diameter: 4"

### **AF/AFG Burner Models**

CHASSIS	MOTOR	IGNITER	PUMP	PRIMARY	ACCESSORIES	
AFG B2007	PSC	Solid-State	Clean-Cut Single-stage	Genisys 7505B1500		
AFG B2008	PSC	Solid-State	Clean-Cut Single-stage	Genisys 7505P152M	Contractor Tool 52082 and Mounting Bracket	
AFG B2005	PSC	Solid-State	Clean-Cut Two-stage	Genisys 7505P1530		
AF B3001	PSC	Solid-State	Clean-Cut Single-stage	Genisys 7505P1500		

### **AF/AFG Burner Accessories**

PART No.	ITEM	DESCRIPTION			
5432	Flange Kit	Universal Flange Kit – Flange & Gasket			
5850	Flange Kit	Split Flange & Gasket			
5685	Pedestal Kit	Universal Pedestal Kit			
5606	Pedestal Kit	Extended Pedestal Kit for 8" – 13" above floor			
51747	Air Boot Kit	Kit with Air Boot / Vacuum relief damper / OA Hood			
7575*	Genisys Control	Epoxy potted for high-moisture applications (* = order Pre- and Post-Purge times for your application)			
5207301U	Cover Kit	Sound Reducing and Tamper Resistant Cover			
51621	Start Helper	Smoother lighting for cold oil conditions			

#### **Universal Air Tube Combination**

FIRING RATE MIN-MAX GPH	BURNER HEAD	USABLE AIR TUBE LENGTH "A"										
		4-1/2"	5"	5-3/8"	6-5/8"	7"	7-1/4"	9"	9"	10-1/2"	13"	16"
Less Head 0.40 - 0.75 0.75 - 1.25 0.85 - 1.65 1.10 - 2.00 1.65 - 2.50 2.50 - 3.00	Less F0 F3 F6 F12 F22 F31	AF44 AF44XR AF44XN AF44YB AF44XO AF44XP AF44XS	- - - - -	AF53 AF53XR AF53XN AF53YB AF53XO AF53XP AF53XS	AF65 AF65XR AF65XN AF65YB AF65XO AF65XP AF65XS	- - - - -	AF72 AF72XR AF72XN AF72YB AF72XO AF72XP AF72XS	AF90 AF90XR AF90XN AF90YB AF90XO AF90XP AF90XS	- - - - -	AF104 AF104XR AF104XN AF104YB AF104XO AF104XP AF104XS	AF130 AF130XR AF130XN AF130YB AF130XO AF130XP AF130XS	AF160 AF160XR AF160XN AF160YB AF160XO AF160XP AF160XS
0.40 - 1.00 0.75 - 2.75	L1 V1	-	AFG50MB AFG50MD	- -	- -	AFG70MB AFG70MD	-	- -	AFG90MB AFG90MD	- -	-	- -