

ZP76KCE-TF5

HFC, R-410A, 60 Hz, 3 - Phase, 200/230 V , [Also Available with Variable Frequency Drives](#)

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45.00	45
Condensing Temp. (°F)	130.00	100
Return Gas Temp. (°F)	65.00	65
Liquid Temp. (°F)	115.00	85
Capacity (BTU/hr)	77000	93700
Power (W):	7060	5020
Current (Amps):	20.8	17
EER(BTU/Wh):	10.9	18.7
Mass Flow (lbs/hr):	1135	1160
Sound Data @		
Sound Power (dBA):	75 Avg	80 Max
Vibration mils(peak-peak):	2.5 Avg	3.5 Max
Record Date:	2009-02-16	
Mechanical		
Displacement (in^3/Rev):	4.32	
Displacement (ft^3/Hr):		
Overall Length (in):	9.70	
Overall Width (in):	9.90	
Overall Height (in):	17.40	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	
Mounting Height (in):	18.20	

Suction Size (in),Type:	1 1 / 4 Rotalock
Discharge Size (in),Type:	1 Rotalock
Initial Oil Charge (oz):	57
Oil Recharge (oz):	56
Oil Type:	3MA
Net Weight (lbs):	87.0
Internal Free Volume (in^3):	264.5

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical	
LRA High* (Amps):	164
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	39
Max Operating Current (Amps):	34.70
RLA, MCC/1.4(use for contactor selection)(Amps):	27.9
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	25.0
RPM:	3500
Box IP :	21
UL File No:	SA2337-19930726
UL File Date:	1993-07-26

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors					
Type	Part No	Low MFD	High MFD	Volts	User Description
No data available in table					

Alternate Applications				
Refrigerant	Voltage	Phase	Frequency	Application
R-410A HFC	200/220	3	50	Air Conditioning

Nomenclature

Family Series

Z: Scroll

Application Range

P: A/C - R-410A/B

Capacity

76K: Capacity Multiplier-1000

Model Variation

C: Model Variation

Oil Type

E: Polyol Ester

Motor Type

T: 3 Phase

Motor Protection

F: Internal Inherent Protection

Voltage

5: 60Hz (200/230-3) 50Hz (200/220-3)