

# WHOLE HOUSE HUMIDIFIERS for Complete Indoor Comfort... ...GET IN THE COMFORT ZONE

## Bypass Humidifier

**MODEL #919599** - Capacity 16.8 gpd

**MODEL #919598** - Capacity 12.0 gpd

## Power Humidifier

**MODEL #919600** - Capacity 18.0 gpd

### Features

- Color Matched to NORDYNE Equipment
- Shipped with field applied logos for all NORDYNE Residential Brands



# Specifications

## Bypass Humidifier —

Model #919599  
& Model #919598

- Plenum mounted humidifier that can be installed on either the Cold Air Return or Warm Air Supply plenum.
- Unit to be constructed of glass filled polyester thermoset material.
- Overall Dimensions of unit are:
 

<b>Model #919599</b>	<b>Model #919598</b>
Width — 13 1/8"	Width — 12 7/8"
Height — 15 1/2"	Height — 12 3/4"
Depth — 9 1/8"	Depth — 9 1/8"
- Plenum opening size:
 

<b>Model #919599</b>	<b>Model #919598</b>
Width — 9 3/4"	Width — 9 3/8"
Height — 12 1/2"	Height — 9 1/2"
- Bypass size to accept a 6" round elbow or straight duct.
- Water Feed Rate:
 

<b>Model #919599</b>	<b>Model #919598</b>
6 Gallons Per Hour	3 Gallons Per Hour
- Evaporative Rate:
 

<b>Model #919599</b>	<b>Model #919598</b>
0.70 Gallons Per Hour @ 120 degree plenum temperature	0.50 Gallons Per Hour @ 120 degree plenum temperature

0.2" WC static pressure difference between supply and return ductwork.
- Size home in square feet based on 8' ceiling:
 

Loose construction (2 air changes per hour) —	
<b>Model #919599</b>	<b>Model #919598</b>
1,000 Sq. Ft.*	750 Sq. Ft.*
Average construction (1 air change per hour) —	
<b>Model #919599</b>	<b>Model #919598</b>
2,000 Sq. Ft.*	1,500 Sq. Ft.*
Tight construction (1/2 air change per hour) —	
<b>Model #919599</b>	<b>Model #919598</b>
4,000 Sq. Ft.*	3,000 Sq. Ft.*
- Drain connection: 1/2" I.D. plastic hose direct to drain fitting on unit.
- Water panel replacement part number:
 

<b>Model #919599</b>	<b>Model #919598</b>
#RP0035	#RP0010
Water Panel	Water Panel
- Electrical Data: 24V - 60HZ - 0.05 Amp
- UL Approved.

## Power

## Humidifier — Model #919600

- Plenum mounted humidifier that can be installed on Warm Air Supply plenum.
- Unit to be constructed of ABS/poly-carbonate thermoplastic material.
- Overall Dimensions of unit are:
 

Width — 15 29/32"
Height — 15 31/32"
Depth — 10 11/32"
- Plenum opening size:
 

Width — 14 7/8"
Height — 14 3/16"
- Water Feed Rate: 6 Gallons Per Hour
- Evaporative Rate: 0.75 Gallons Per Hour @ 120 degree plenum temperature.
- Size home in square feet based on 8' ceiling:
 

Loose construction (2 air changes per hour) —	1,050 Sq. Ft.*
Average construction (1 air change per hour) —	2,100 Sq. Ft.*
Tight construction (1/2 air change per hour) —	4,200 Sq. Ft.*
- Drain connection: 1/2" I.D. plastic hose direct to drain fitting on unit.
- Water panel replacement part number: #RP0035 Water Panel.
- Electrical Data: 120V - 60HZ - 0.70 Amp
- UL Approved.

### \*Calculations based on:

- 20 degree F and 70% RH outside air.
- 70 degree F and 35% RH room temperature air.
- Internal moisture gain of 1 lb./hr.
- 70% blower operation.



24V Humidistat

Accessories Included on both Humidifiers:

- 24V Humidistat
- Saddle Valve

Transformer Also Included on Bypass Humidifier



Specifications and illustrations subject to change without notice and without incurring obligation.

©2011 NORDYNE. All Rights Reserved.

158D-0311

Printed in U.S.A.

1-800-4AC-HEAT or 1-877-372-7808

www.nordyne.com



Universal HVAC Parts & Accessories