



Model: RGA5471BXC

Product Description

Type: Rotary
Application: HBP/AC - Air Conditioning
Refrigerant: R-410A
Voltage/Frequency: 220-240V ~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	220V ~ 50HZ	5750	1449	1685	624	9.21	2.32	2.7	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

General

Evaporating Temp. Range: -23.3°C to 12.8°C (-10°F to 55°F)
Motor Torque: Low Start Torque (LST)
Compressor Cooling: Fan

Mechanical

Weight: 25
Weight Unit of Measure: LB
Displacement (cc): 7.121
Oil Type: Polyvinylether
Viscosity (cSt): 68
Oil Charge (cc): 290

Electrical

Voltage Range (50 Hz): 198-264
Voltage Range (60 Hz): N/A
Locked Rotor Amps (LRA): 18.8
Rated Load Amps (RLA 50 Hz): 2.77
Rated Load Amps (RLA 60 Hz): 0
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: 4.27
Motor Resistance (Ohm) - Start: 10.74
Motor Type: CSR
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed