

## Ruud Ultra™ Series Variable Speed Air Conditioners



### UA20 Series

Efficiencies up to 20.5 SEER/14.5 EER

Nominal Sizes 2, 3, 4 & 5 Ton

[7.03, 10.6, 14.06 & 17.6 kW]

Cooling Capacities 17.3 to 60.5 kBtu  
[5.7 to 17.7 kW]



*"Proper sizing and installation of equipment is critical to achieve optimal performance. Split system air conditioners and heat pumps must be matched with appropriate coil components to meet Energy Star. Ask your Contractor for details or visit [www.energystar.gov](http://www.energystar.gov)."*



- **PlusOne™ Energy** Efficiency offers minimum of 20 SEER and 13 EER system performance across all capacities.
- **PlusOne™ Expanded Valve Space** – 3"-4"-5" service valve space – provides a minimum working area of 27-square inches for easier access
- **PlusOne™ Triple Service Access** – 15" wide, industry leading corner service access – makes repairs easier and faster. The three fastener removable corner allows optimal access to internal unit components. Individual louver panels come out once fastener is removed, for faster coil cleaning and easier cabinet reassembly
- **EcoNet® Enabled product.** The EcoNet Smart Home System provides advanced air & water control for maximum energy savings and ideal comfort.
- New composite base pan – dampens sound, captures louver panels, eliminates corrosion and reduces number of fasteners needed
- Powder coat paint system – for a long lasting professional finish
- The Copeland Scroll™ Variable Speed Compressor has a modulating technology which provides more precise temperature control, lower humidity and greater efficiency. The overdrive feature provides cooling load up to 107°F.
- Modern cabinet aesthetics – increased curb appeal with visually appealing design
- Curved louver panels – provide ultimate coil protection, enhance cabinet strength, and increased cabinet rigidity
- Optimized fan orifice – optimizes airflow and reduces unit sound
- Rust resistant screws – confirmed through 1500-hour salt spray testing
- Diagnostic service window with two-fastener opening – provides access to the high and low pressure.
- External gauge port access – allows easy connection of "low-loss" gauge ports
- Single-row condenser coil (up thru 4 tons) – makes unit lighter and allows thorough coil cleaning to maintain "out of the box" performance
- 35% fewer cabinet fasteners and fastener-free base – allow for faster access to internal components and hassle-free panel removal
- Service trays – hold fasteners or caps during service calls
- QR code – provides technical information on demand for faster service calls
- Fan motor harness with extra long wires allows unit top to be removed without disconnecting fan wire.
- High and low pressure standard on all models.

## TABLE OF CONTENTS

Standard Feature .....	3
Available SKUs .....	3
Features & Benefits .....	4-8
Model Number Identification .....	9-10
General Data/Electrical Data .....	11
Accessories .....	12
Weighted Sound Power .....	12
Smart Home Systems .....	13
Unit Dimensions.....	14
Clearances.....	15
Wiring Diagrams .....	16
Refrigerant Line Size Information .....	17-18
Performance Data .....	19-22
Guide Specifications .....	23
Limited Warranty .....	24

## Standard Feature Table

Feature	STANDARD FEATURES			
	24	36	48	60
R-410A Refrigerant	√	√	√	√
Maximum SEER	20.5	20.5	20.5	20.5
Maximum EER	13	13	13	13
EcoNet Enabled	√	√	√	√
Copeland Scroll™ Variable Speed Compressor	√	√	√	√
Compressor Sound Blanket	√	√	√	√
Variable speed outdoor fan motor	√	√	√	√
Swept wing fan blade	√	√	√	√
Field Installed Filter Drier	√	√	√	√
Front Seating Service Valves	√	√	√	√
Internal Pressure Relief Valve	√	√	√	√
Internal Thermal Overload	√	√	√	√
Low Ambient capability	√	√	√	√
3-4-5 Expanded Valve Space	√	√	√	√
Composite Basepan	√	√	√	√
1" Screw Control Box Access	√	√	√	√
15" Access to Internal Components	√	√	√	√
Quick release louver panel design	√	√	√	√
No fasteners to remove along bottom	√	√	√	√
Optimized Venturi Airflow	√	√	√	√
Single row condenser coil	√	√	√	2 Row
Powder coated paint	√	√	√	√
Rust resistant screws	√	√	√	√
QR code	√	√	√	√
External gauge ports	√	√	√	√
Service trays	√	√	√	√

√ = Standard

## Available SKUs

Available Models	Description
UA2024AJVCB	2 ton EcoNet® Enabled Inverter Driven Ruud <i>Ultra™</i> Series Variable Speed Air Conditioner-208/230/1/60
UA2036AJVCB	3 ton EcoNet® Enabled Inverter Driven Ruud <i>Ultra™</i> Series Variable Speed Air Conditioner-208/230/1/60
UA2048AJVCB	4 ton EcoNet® Enabled Inverter Driven Ruud <i>Ultra™</i> Series Variable Speed Air Conditioner-208/230/1/60
UA2060AJVCB	5 ton EcoNet® Enabled Inverter Driven Ruud <i>Ultra™</i> Series Variable Speed Air Conditioner-208/230/1/60

## Introduction to UA20 Air Conditioner


The UA20 is our EcoNet® Enabled, Inverter Driven *Ultra*™ Series Variable Speed Air Conditioner and is part of the Ruud Air Conditioner product line that extends from 13 to 20 SEER. This highly featured and reliable air conditioner is designed for years of dependable, efficient operation when matched with Ruud indoor aluminum evaporator coils and furnaces or air handler units with aluminum evaporators.

**⚠ WARNING: This product is not approved for installation at 2000 meters (6,561 feet) above sea level or higher. Installation at higher altitudes may result in control and unit failures due to electrical arc tracking between electrical components on the inverter drive control board possibly resulting in fire, electrical shock, property damage, personal injury or death.**

The *Ultra*™ Series UA20 is part of a new line of Ruud smart heating, cooling and water heating products. Using the latest in sensor technology and a powerful EcoNet® monitoring system, Ruud provides homeowners with a new level of protection, control and energy savings. Ruud smart heating, cooling and water heating products will alert the homeowner if there is ever an issue via the EcoNet Smart Thermostat (1) and the EcoNet Mobile app. The EcoNet Mobile App makes it easy for homeowners to manage their home comfort environment at home or on-the-go,\* while enjoying the convenience and savings benefits of a highly efficient system.



Along with the EcoNet Smart Home System the UA20 is matched with the RHMV Constant CFM Variable Speed EcoNet Enabled Air Handler (3) or can be applied in a Furnace application with the EcoNet Enabled Two-Stage Variable Speed U802V or U96V Gas Furnaces or the fully modulating U97V and RCF Aluminum Cased Furnace Coils with EEV (4). See individual specification documents for more details of the indoor products.




\*WiFi broadband internet connection required. Download the EcoNet App from the App Store or Google Play to set up your EcoNet Smart Thermostat. Receipt of notifications depend on home WiFi set up. WiFi broadband internet connection required.



## How It Works

The UA20 *Ultra*™ Series Inverter Driven Variable Speed Air Conditioner's (5) variable speed outdoor unit control (VSODU) (6) continuously monitors the EcoNet control temperature and humidity set point, suction pressure (7), suction temperature (8), outdoor coil temperature (9) and outdoor temperature (10) and feeds this information to the Copeland Inverter Control Motor Drive (11). The Copeland Inverter Control Motor Drive converts AC to DC power, sends it to the Copeland Scroll™ variable speed compressor (12) Brushless Permanent Magnet motor (BPM), dynamically adjusting its speed. Simultaneously the VSODU provides input to the ECM outdoor fan motor (13)

which is equipped with the latest swept wing fan technology (14) and the Electronic Expansion Valve (EEV) (15) which syncs up with the compressor speed to deliver the exact capacity the home needs to meet its comfort requirements. The result of this advanced technology is significantly improved energy efficiency and comfort. Energy efficiency is improved by precise load matching, less cycling on and off and low amp gradual compressor, outdoor and indoor motor operation. Comfort is improved by precise temperature control, precise humidity control and extra capacity during extreme summer and cold weather conditions.



## System Component Descriptions

**EcoNet Smart Thermostat – (1):** The EcoNet Smart Thermostat serves as the hub of communication for a home’s Heating, Cooling and Water Heating systems and is required to operate an EcoNet Enabled Heating and Cooling system in a fully communicating mode. The EcoNet Smart Thermostat displays detail diagnostic from outdoor and indoor connected units.

**Variable Speed Outdoor Unit Control (VSODU) – (6)** is where control wiring is hooked to the UA20. The VSODU control takes input from the EcoNet Control Center, outdoor suction temperature and pressure sensors, outdoor air temperature and communicates to the Copeland Inverter Control Motor Drive, EEV, outdoor fan and indoor blower to precisely control system capacity output of the air conditioner cooling mode. It also is equipped with Dual Seven-Segment Display for technician interface, operation status and fault code communication. Two momentary buttons allow technician to initiate various operating modes. Various LED’s communicate active EcoNet communication, microprocessor activity and EEV operation. See I&O for more details.

**The Copeland Inverter Control Motor Drive – (11)** converts incoming single-phase AC power to 3 phase DC simulated sine wave power. Once power is converted the Copeland Inverter Control Motor Drive varies frequency of the power to the compressor varying the compressor speed. The Copeland Inverter Control Motor Drive has active protection algorithms that keep the compressor safely inside its operating envelope.

**The Copeland Scroll™ Variable Speed compressor – (12)** utilizes a Brushless Permanent Magnet Motor (BPM) that varies the Scroll speed, thus, varying the refrigerant flow. The robust scroll design has proven reliability over competing compressor technologies.

**Swept Wing Fan Blade – (14)** is the latest technology in outdoor fans that increase efficiency and reduces air noise.

**The Electronic Expansion Valve (EEV) –** (Located on the indoor coil) is an electronically driven refrigerant control valve. A small stepper motor is used to open and close the valve to precisely control refrigerant flow. It is controlled by the EcoNet Air Handler Control or stand alone EEV Control in furnace coil applications. Either control receives input from the pressure transducer and suction sensor to control the refrigerant in the cooling mode. The EEV is superior to a TXV (thermostatic expansion valve) because the EEV controls superheat at the evaporator coil under varying load and refrigerant flow conditions, more precisely than traditional TXV’s.

**The Filter – (16)** is an electrical device that “cleans” the AC power component. This low pass filter only permits the passage of 60-Hertz signal to the inverter drive.

**The Pressure Transducer – (7)** is used to measure suction pressure in the outdoor air conditioner. The VSODU takes this input to operate low pressure and make decisions on system operation such as low ambient cooling.

**Various temperature sensors –** There is an outdoor air sensor (10), an outdoor coil sensor (9), a discharge line temperature sensor (not shown, located on discharge line), a suction line temperature sensor (8) and a compressor sump temperature sensor (not shown, located bottom of compressor). The VSODU uses these temperature measurements to operate the system.


**The Choke – (17)** is provided to absorb power spikes that might occur on the DC line.

**Ferrite Rings – (18)** are iron cores through which AC power is looped keeping any electrical noise contained. They also reduce the induction of electrical transient into the DC drive.

**The Suction Accumulator – (19)** prevents liquid refrigerant from entering the compressor.


## Features

In addition all UA20 *Ultra*™ Series inverter driven Variable Speed Air Conditioners have the following features:




Our unique composite base (3) reduces sound emission, eliminates rattles, significantly reduces fasteners, eliminates corrosion and has integrated brass compressor attachment inserts (4). Furthermore it has incorporated into the design, water management features, means for hand placement (5) for unit maneuvering, screw trays (6) and inserts for lifting off unit pad. (7)

Service Valves (8) are rigidly mounted in the composite base with 3" between suction and discharge valves, 4" clearance below service valves and a minimum of 5" above the service valves, creating industry leading ease of installation. The minimum




27 square-inches around the service valves allows ample room to remove service valve schrader prior to brazing, plenty of clearance for easy brazing of the suction and discharge lines to service valve outlets, easy access and hookup of low loss refrigerant gauges (9), and access to the service valve caps for opening.

Controls are accessed from the corner of the unit by removing only one fastener from the control access cover, revealing the industry's largest 15" wide and 22" tall control area (10). With all this room in the control area the high voltage electrical whip (11) can easily be inserted through the right size opening in the bottom of the control area. Routing it leads directly to lugs for connection. The low voltage control wires (12) are easily connected to the units VSODU terminal strip. The service window (14) can be removed by removing two screws to view the interior of unit. (15) (High and low pressure is standard on UA20 models). If in the rare event, greater access is needed to internal compo-




nents, such as the compressor, the entire corner of the unit can be removed along with the top cover assembly to have unprecedented access to interior of the unit (16). Extra wire length is incorporated into each outdoor fan and compressor so top cover and control panel can be positioned next to the unit. Or with minimal effort the plug can be removed from the compressor and the outdoor fan wires can be removed from the VSODU to allow even more uncluttered access to the interior of the unit



(17). Outdoor coil heights range from as short as 35" to 48". Disassembly to this degree and complete reassembly only takes a first time service technician less than 10 minutes. (17)

All units utilize formed louver panels which provide industry leading coil protection. Louver removal for coil cleaning is accomplished by removing one screw and lifting the panel out of the composite base pan. (19) All UA20 2, 3, 4 ton units utilize single row coils (18) making cleaning easy and complete, restoring the performance of the air conditioner back to out of the box performance levels year after year.




The outdoor fan motor has sleeve bearings and is inherently protected. The motor is totally enclosed for maximum protection from weather, dust and corrosion. (20) Access to the outdoor fan is made by removing four fasteners from the fan grille. The outdoor fan can be removed from the fan grille by removing 4 fasteners in the rare case outdoor fan motor fails.

Each cabinet has optimized composite (21) fan orifice assuring efficient and quiet airflow.



The entire cabinet has post powder paint (22) achieving 1000 hour salt spray rating, allowing the cabinet to retain its aesthetics throughout its life.



The Copeland Scroll™ Variable Speed compressors with standard internal pressure relief and internal thermal overload are used on all capacities assuring longevity of high efficient and quiet operation for the life of the product. All UA20 Air Conditioner come standard with high and low pressure switches reinforced vinyl compressor sound covers containing a 1½ inch thick batt of fiberglass insulation and open edges are sealed with a 1 inch wide hook and loop fastening tape for superior sound quality.

## Features (con't.)

Each unit is shipped with filter drier for field installation and will trap any moisture or dirt that could contaminate the refrigerant system.



All cabinets have industry leading structural strength due to the composite base pan (23), interlocking corner post (24), formed curved louver panels (25) and drawn top cover (26) making it the most durable cabinet on the market today.

Each UA20 capacity has undergone rigorous psychometric testing to assure performance ratings of capacity, SEER and EER per AHRI Standard 210/240 rating conditions. Also each unit bears the UL mark and each unit is certified to UL 1995 safety standards.



Each unit has undergone specific strain and modal testing to assure tubing (27) is outside the units natural frequency and that the suction and discharge lines connected to the compressor withstand any starting, steady state operation, or shut down forces imposed by the compressor.

All units have been sound tested in sound chamber to AHRI 270 rating conditions, and A-weighted Sound Power Level tables produced, assuring units have acceptable noise qualities (see page 12). Each unit has been ran in cooling operation at 95°F and sound ratings for the UA20 range from as low as 68 dBA at low speed and as high as 76 dBA at 95°F rated conditions.

All units have been ship tested to assure units meet stringent “over the road” shipping conditions.

As manufactured, all units in the UA20 family have cooling capability to 40°F. Addition of low ambient control will allow the unit to operate down to 0°F. Factory testing is performed on each unit. All component parts meet well defined specification and continually go through receiving inspections. Each component installed on a unit is scanned, assuring correct component utilization for a given unit capacity and voltage. All condenser coils are leak tested with pressurization test to 550#’s and once installed and assembled, each units’ complete refrigerant system is helium leak tested. All units are fully charged from the factory for up to 15 feet of piping. All units are factory run tested. The UA20 has a 10-year conditional unit replacement warranty (registration required) and a 10 year limited parts warranty.

## Required Control EcoNet Smart Thermostat



UETST700SYS

The EcoNet Smart Thermostat serves as the hub of communication for a home’s Heating, Cooling and Water Heating systems, and is required to operate an EcoNet Enabled Heating & Cooling system in a fully communicating mode.

## Air Conditioners\*

U	A	20	24	A	J	V	C	B	*
Brand	Product Category	SEER	Capacity BTU/HR	Major Series*	Voltage	Type	Controls	Minor Series**	Option Code
Ruud	A - Air Conditioners	13 - 13 SEER 14 - 14 SEER 16 - 16 SEER 17 - 17 SEER 20 - 20 SEER	18 - 18,000 [5.28 kW] 24 - 24,000 [7.03 kW] 30 - 30,000 [8.79 kW] 36 - 36,000 [10.55 kW] 42 - 42,000 [12.31 kW] 48 - 48,000 [14.07 kW] 60 - 60,000 [17.58 kW]	A - 1st Design B - 2nd Design	J - 1ph, 208-230/60 C - 3ph, 208-230/60	1 - Single-stage 2 - Two-stage V - Inverter	C - Communicating N - Non-Communicating	B - High and low pressure control	N/A

\*See page 3 for available SKU's.

†Two-stage and inverter available in whole capacities only.

## Heat Pumps (For Reference)\*\*

U	P	20	24	A	J	V	C	A	*
Brand	Product Category	SEER	Capacity BTU/HR	Major Series*	Voltage	Type	Controls	Minor Series**	Option Code
Ruud	P - Heat Pump	13 - 13 SEER 14 - 14 SEER 15 - 15 SEER 17 - 17 SEER 20 - 20 SEER	18 - 18,000 [5.28 kW] 24 - 24,000 [7.03 kW] 30 - 30,000 [8.79 kW] 36 - 36,000 [10.55 kW] 42 - 42,000 [12.31 kW] 48 - 48,000 [14.07 kW] 60 - 60,000 [17.58 kW]	A - 1st Design	J - 1ph, 208-230/60 C - 3ph, 208-230/60 D - 3ph, 460/60	1 - Single-stage 2 - Two-stage V - Inverter P - Piston	C - Communicating N - Non-Communicating	A - 1st Design	N/A

†Two-stage and inverter available in whole capacities only.

## Furnace Coils (For Reference)\*\*

R	C	F	24	17	S	E	A	M	C	A	*
Brand	Product Category	Type	Capacity BTU/HR	Width	Efficiency	Metering Device	Major Series*	Orientation	Casing	Minor Series**	Option Code
Ruud	C - Evap Coil	F - Furn Coil H - Air-Handler Coil	24 - 24,000 [7.03 kW] 36 - 36,000 [10.55 kW] 48 - 48,000 [14.07 kW] 60 - 60,000 [17.58 kW]	14 - 14" 17 - 17.5" 21 - 21" 24 - 24.5"	S - Standard Eff. M - Mid Eff. H - High Eff.	T-TXV E-EEV P-Piston	A - 1st Design	M - Multipoise V - Vertical only/ H - Ded. convertible Horizontal only	C - Cased U - Uncased	A - 1st Design	N/A

NOTE: The above Model Number ID's are for reference only. Available SKU's are listed on the standard features/available SKU page of model spec sheet.

[ ] Designates Metric Conversions

**90%+ AFUE Gas Furnaces (For Reference)\*\***

<u>U</u>	<u>96</u>	<u>V</u>	<u>A</u>	<u>70</u>	<u>2</u>	<u>3</u>	<u>17</u>	<u>M</u>	<u>S</u>	<u>A</u>
Brand	Series	Motor	Major Rev	Input BTU/HR	Stages	Air Flow	Cabinet Width	Configuration	Nox	Minor Rev
Ruud	90 - 90 AFUE 92 - 92 AFUE 95 - 95 AFUE 96 - 96 AFUE (X-13) 97 - 97 AFUE	V - Variable speed T - Constant Torque (X-13) P - PSC	A - 1st Design	040 - 42,000 [12.31 kW] 060 - 56,000 [16.41 kW] 070 - 70,000 [20.51 kW] 085 - 84,000 [24.62 kW] 100 - 98,000 [28.72 kW] 115 - 112,000 [32.82 kW]	1 - Single-stage 2 - Two-stage M - Modulating	3 - up to 3 ton 5 - 3 1/2 up to 5 ton	14 - 14" 17 - 17.5" 21 - 21" 24 - 24.5"	M - Multi	X - Low Nox S - Standard	A - 1st Design

**80% AFUE Gas Furnaces (For Reference)\*\***

<u>U</u>	<u>80</u>	<u>2</u>	<u>V</u>	<u>A</u>	<u>075</u>	<u>3</u>	<u>17</u>	<u>M</u>	<u>S</u>	<u>A</u>
Brand	Series	Stages	Motor	Major Rev	Input BTU/HR	Air Flow	Cabinet Width	Configuration	Nox	Minor Rev
Ruud	80 - 80+ AFUE	1 - Single-stage 2 - Two-stage	V - Variable speed T - Constant Torque (X-13) P - PSC premium S - PSC standard	A - 1st Design	050 - 50,000 [15 kW] 075 - 75,000 [22 kW] 100 - 100,000 [29 kW] 125 - 125,000 [37 kW] 150 - 150,000 [44 kW]	3 - up to 3 ton 4 - 2 1/2 to 4 ton 5 - 3 1/2 up to 5 ton	14 - 14" 17 - 17.5" 21 - 21" 24 - 24.5"	M - Multi D - Down Z - Down & zero clearance down flow	X - Low Nox S - Standard	A - 1st Design

**Air Handlers (For Reference)\*\***

<u>R</u>	<u>H</u>	<u>M</u>	<u>V</u>	<u>36</u>	<u>17</u>	<u>S</u>	<u>E</u>	<u>A</u>	<u>C</u>	<u>J</u>	<u>A</u>	<u>000</u>	<u>*</u>	<u>-</u>
Brand	Product Category	Stages of Airflow	Motor Type	Capacity BTU/HR	Width	Coil Size	Metering Device	Major Series*	Controls	Voltage	Minor Series**	Factory Heat Cap	Option Code	
Ruud	H - Air Handler	1 - Single-Stage 2 - Two-Stage M - Modulating	V - Variable Speed T - Constant Torque P - PSC	24 - 24,000 [7.03 kW] 36 - 36,000 [10.55 kW] 48 - 48,000 [14.07 kW] 60 - 60,000 [17.58 kW]	14 - 14" 17 - 17.5" 21 - 21" 24 - 24.5"	S - Standard Eff. M - Mid Eff. H - High Eff.	T - TEV E - EEV P - Piston	A - 1st Design	C - Communicating N - Non-comm	J - 1ph, 208-240/60	A - 1st Design	00 - no factory heat with option code	*TBD	

NOTE: The above Model Number ID's are for reference only. Available SKU's are listed on the standard features/available SKU page of model spec sheet.

**[ J ] Designates Metric Conversions**

<b>Physical Data</b>				
Model No.	UA2024A	UA2036A	UA2048A	UA2060A
Nominal Tonnage	2.0	3.0	4.0	5.0
<b>Valve Connections</b>				
Liquid Line O.D. – in.	3/8	3/8	3/8	3/8
Suction Line O.D. – in.	3/4	3/4	7/8	7/8
Refrigerant (R-410A) furnished oz. <sup>1</sup>	148	193.6	196	376
Compressor Type	Scroll			
<b>Outdoor Coil</b>				
Net face area – Outer Coil	22.2	22.3	32.5	32.5
Net face area – Inner Coil	—	—	—	—
Tube diameter – in.	3/8	3/8	3/8	3/8
Number of rows	1	1	1	2
Fins per inch	20	20	22	20
<b>Outdoor Fan</b>				
Diameter – in.	24	24	26	26
Number of blades	3	3	3	3
Motor hp	1/5	1/3	1/2	1/2
CFM	3330	4315	6240	6175
RPM	772	825	935	900
watts	83	114	278	278
Shipping weight – lbs.	226	244	263	316
Operating weight – lbs.	214	236	255	308
<b>Electrical Data</b>				
Line Voltage Data (Volts-Phase-Hz)	208/230-1-60	208/230-1-60	208/230-1-60	208/230-1-60
Maximum overcurrent protection (amps) <sup>2</sup>	35	45	70	80
Minimum overcurrent protection (amps) <sup>2</sup>	25	35	60	60
Minimum circuit ampacity <sup>3</sup>	21	29	46	48
<b>Compressor</b>				
Rated load amps	15	20.1	32	34.1
Locked rotor amps	35	35	50	50
<b>Condenser Fan Motor</b>				
Full load amps	1.4	3.5	5.3	5.3
Locked rotor amps	N/A	N/A	N/A	N/A

<sup>1</sup>Refrigerant charge sufficient for 15 ft. length of refrigerant lines. For longer line set requirements see the installation instructions for information about set length and additional refrigerant charge required.

<sup>2</sup>HACR type circuit breaker or fuse.

<sup>3</sup>Refer to National Electrical Code manual to determine wire, fuse and disconnect size requirements.

## Accessories

Model No.	UA2024	UA2036	UA2048	UA2060
EcoNet Smart Thermostat	UETST700SYS	UETST700SYS	UETST700SYS	UETST700SYS
Compressor sound cover	STD	STD	STD	STD

## Weighted Sound Power Level (dBA)

VS ODU	Stage	Standard Rating (dBA)	TYPICAL OCTAVE BAND SPECTRUM (dBA without tone adjustment)						
			125	250	500	1000	2000	4000	8000
(-)A2024	High	68	47.1	47.7	58.8	57.1	55.0	52.7	45.6
	Low	58.9	29	36.5	42	45.7	42.3	43.2	33
(-)A2036	High	72	42.9	52.8	62.7	63.6	58.7	54.1	52.4
	Low	57	29.2	36.7	44.9	45.4	42.2	39.4	32.2
(-)A2048	High	72	48.2	55.3	64.6	61.7	56.2	51.7	46.2
	Low	54	30.6	39	42.2	42.5	36.5	35.2	35
(-)A2060	High	76	50.7	62.7	67.7	65.4	64.2	59.2	54.9
	Low	70	46.6	50.5	62.7	52.9	49.4	46	41.4

NOTE: Tested in accordance with AHRI Standard 270-08 (not listed in AHRI)



## THE ECONET® SMART THERMOSTAT

**BUILT-IN WIFI**

**4.3" LCD TOUCH SCREEN**

**LOCAL WEATHER** – Current conditions plus 6-day forecast

**5 OPERATING MODES** – Heat, Cool, Auto, Emergency Heat and Fan Only

**7-DAY PROGRAMMABLE SCHEDULE** – Offers comfort without thought

**ONE-TOUCH AWAY** – Quickly switch to your energy-saving away preferences

**VACATION SCHEDULING** – Allows you to save while you're away and come home to comfort

**MOTION SENSOR** – Automatically wakes the screen as you approach

**STANDBY SCREEN** – Displays indoor temperature and current weather



**UETST700SYS**

## OPERATIONAL FEATURES

**AUTOMATIC CHANGEOVER** – Transitions between heating and cooling automatically to keep the house comfortable

**INTEGRATED WATER CONTROL** – Enables easy water heater management

**SMOOTH ARRIVAL** – Prompts the system to start ahead of schedule to ensure the home is at the desired temperature at the scheduled time

**HUMIDITY CONTROL** – Supports humidifier accessories or over-cool based dehumidification

**DETAILED OPERATING STATUS** – View pertinent equipment status information and run times

**CONTINUOUS FAN** – Offers 5 speeds (Low, Medium Low, Medium, Medium High, High)

**SHORT-CYCLE PROTECTION** – Avoids damage to equipment from short run cycles

## MONITORING & REMOTE CONTROL FEATURES

**ACTIVE MONITORING** – Alerts to problems that need immediate attention

**REMOTE CONTROL** – Allows adjusting of comfort and settings from anywhere using a mobile device

**SERVICE ALERTS** – Sends routine maintenance reminders

**AIR FILTER MONITORING** – Detects when it's time to replace the air filter

**ALARM HISTORY** – Displays time-stamped alarm codes with clear descriptions


## ECONET SMART THERMOSTAT COMPATIBILITY

Heating & Cooling										
Models	Gas Furnaces				Air Handlers		Air Conditioners		Heat Pumps	
	U802V	U96V	U97V	U98V	RHMV	RH2T	UA20	UA17*	UP20	UP17
UETST700SYS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

\*Models not EcoNet Enabled: RA1724AJ2NB, RA1736AJ2NB, RA1748AJ2NB, RA1760AJ2NB

## Unit Dimensions



MODEL NO.	OPERATING						SHIPPING					
	H (Height)		L (Length)		W (Width)		H (Height)		L (Length)		W (Width)	
	INCHES	mm	INCHES	mm	INCHES	mm	INCHES	mm	INCHES	mm	INCHES	mm
UA2024	39	990	33.75	857	33.75	857	41.56	1055	37.64	956	37.56	954
UA2036	39	990	33.75	857	33.75	857	41.56	1055	37.64	956	37.56	954
UA2048	51	1295	35.75	908	35.75	908	53.56	1360	39.37	999	39.64	1006
UA2060	51	1295	35.75	908	35.75	908	53.56	1360	39.37	999	39.64	1006



[ ] Designates Metric Conversions

ST-A1226-02-00


# CLEARANCES



**NOTE: NUMBERS IN ( ) = mm**

**IMPORTANT:** When installing multiple units in an alcove, roof well or partially enclosed area, ensure there is adequate ventilation to prevent re-circulation of discharge air.

## Control Wiring



## Application Guidelines

1. Intended for outdoor installation with free air inlet and outlet. Outdoor fan external static pressure available is less than 0.01 -in. wc.
2. Minimum outdoor operation air temperature for cooling mode without low-ambient operation accessory is 55°F (12.8°C).
3. Maximum outdoor operating air temperature is 125°F (51.7°C).
4. For reliable operation, unit should be level in all horizontal planes.
5. Use only copper wire for electric connections at unit. Aluminum and clad aluminum are not acceptable for the type of connector provided.
6. Do not apply capillary tube indoor coils to these units.
7. Factory – supplied filter drier must be installed.

## Refrigerant Line Sizing Chart (English Units)

20 SEER Variable Speed Air-Conditioners								
Unit Size	Allowable Liquid Line Size	Allowable Suction Line Size	Outdoor Unit ABOVE or BELOW Indoor Unit					
			Equivalent Length (Feet)					
			< 25	26-50	51-75	76-100	101-125	126-150
			Maximum Vertical Rise (Outdoor Unit Below Indoor Unit)* / Capacity Multiplier					
2.0 Ton* SEE NOTE 3	1/4"	5/8"	25/1.00	50/0.99	32/0.98	40/0.97	NR	NR
	5/16"	5/8"	25/1.00	50/0.99	50/0.98	50/0.97	50/0.96	50/0.95
	3/8"	5/8"	25/1.00	50/0.99	50/0.98	50/0.97	50/0.96	50/0.95
	1/4"	3/4**	25/1.00	50/1.00	32/0.99	40/0.99	NR	NR
	5/16"	3/4**	25/1.00	50/1.00	50/0.99	50/0.99	50/0.99	50/0.98
	3/8"	3/4**	25/1.00	50/1.00	50/0.99	50/0.99	50/0.99	50/0.98
3 Ton	5/16"	5/8"	25/0.99	50/0.97	50/0.95	50/0.93	37/0.91	NR
	3/8"	5/8"	25/0.99	50/0.97	50/0.95	50/0.93	50/0.91	NR
	5/16"	3/4"	25/1.00	50/0.99	50/0.99	50/0.98	37/0.97	22/0.96
	3/8"	3/4"	25/1.00	50/0.99	50/0.99	50/0.98	50/0.97	50/0.96
	1/2"	3/4"	25/1.00	50/0.99	50/0.99	50/0.98	50/0.97	50/0.96
4 Ton	3/8"	3/4"	25/0.99	50/0.98	50/0.97	50/0.96	50/0.94	50/0.93
	1/2"	3/4"	25/0.99	50/0.98	50/0.97	50/0.96	50/0.94	50/0.93
	3/8"	7/8"	25/1.00	50/0.99	50/0.99	50/0.98	50/0.98	50/0.97
	1/2"	7/8"	25/1.00	50/0.99	50/0.99	50/0.98	50/0.98	50/0.97
5 Ton	3/8"	3/4"	25/0.99	50/0.97	50/0.95	50/0.93	50/0.91	NR
	1/2"	3/4"	25/0.99	50/0.97	50/0.95	50/0.93	50/0.91	NR
	3/8"	7/8"	25/1.00	50/0.99	50/0.98	50/0.98	50/0.97	38/0.96
	1/2"	7/8"	25/1.00	50/0.99	50/0.98	50/0.98	50/0.97	50/0.96

**NOTES:**

- 1) Do not exceed 150 ft linear line length.
- 2) \* Do not exceed 50 ft vertical separation between indoor and outdoor units.
- 3) \*\* 3/4" suction line should only be used for 2 ton systems if outdoor unit is below or at same level as indoor unit to assure proper oil return.
- 4) Always use the smallest liquid line allowable to minimize refrigerant charge.
- 5) Applications shaded in light gray indicate capacity multipliers between 0.90 and 0.96 which are not recommended, but are allowed.
- 6) Applications shaded in dark gray are not recommended due to excessive liquid or suction pressure drop.

[ ] Designates Metric Conversions

## Refrigerant Line Sizing Chart (Metric Units)

20 SEER Variable Speed Air-Conditioners								
Unit Size	Allowable Liquid Line Size mm [in.]	Allowable Suction Line Size mm [in.]	Outdoor Unit ABOVE or BELOW Indoor Unit					
			Equivalent Length (Meters)					
			< 8	8-15	16-23	24-30	31-38	39-46
Maximum Vertical Rise (Outdoor Unit Below Indoor Unit)*/Capacity Multiplier								
7.0 kW [2.0 Ton]* <b>SEE NOTE 3</b>	6.35 [1/4]	15.88 [5/8]	8/1.00	15/0.99	1/0.98	10/0.97	<b>NR</b>	<b>NR</b>
	7.94 [5/16]	15.88 [5/8]	8/1.00	15/0.99	15/0.98	15/0.97	15/0.96	15/0.95
	9.53 [3/8]	15.88 [5/8]	8/1.00	15/0.99	15/0.98	15/0.97	15/0.96	15/0.95
	6.35 [1/4]	19.05 [3/4]**	8/1.00	15/0.99	10/0.99	1/0.99	<b>NR</b>	<b>NR</b>
	7.94 [5/16]	19.05 [3/4]**	8/1.00	15/0.99	15/0.99	15/0.99	15/0.99	15/0.98
	9.53 [3/8]	19.05 [3/4]**	8/1.00	15/0.99	15/0.99	15/0.99	15/0.99	15/0.98
10.6 kW [3 Ton]	7.94 [5/16]	15.88 [5/8]	8/0.99	15/0.97	15/0.95	15/0.93	11/0.91	<b>NR</b>
	9.53 [3/8]	15.88 [5/8]	8/0.99	15/0.97	15/0.95	15/0.93	15/0.91	<b>NR</b>
	7.94 [5/16]	19.05 [3/4]	8/1.00	15/0.99	15/0.99	15/0.98	11/0.97	7/0.96
	9.53 [3/8]	19.05 [3/4]	8/1.00	15/0.99	15/0.99	15/0.98	15/0.97	15/0.96
	12.7 [1/2]	19.05 [3/4]	8/1.00	15/0.99	15/0.99	15/0.98	15/0.97	15/0.96
14.1 kW [4 Ton]	9.53 [3/8]	19.05 [3/4]	8/0.99	15/0.98	15/0.97	15/0.96	15/0.94	15/0.93
	12.7 [1/2]	19.05 [3/4]	8/0.99	15/0.98	15/0.97	15/0.96	15/0.94	15/0.93
	9.53 [3/8]	22.23 [7/8]	8/1.00	15/0.99	15/0.99	15/0.98	15/0.98	15/0.97
	12.7 [1/2]	22.23 [7/8]	8/1.00	15/0.99	15/0.99	15/0.98	15/0.98	15/0.97
17.6 kW [5 Ton]	9.53 [3/8]	19.05 [3/4]	8/0.99	15/0.97	15/0.95	15/0.93	15/0.91	<b>NR</b>
	12.7 [1/2]	19.05 [3/4]	8/0.99	15/0.97	15/0.95	15/0.93	15/0.91	<b>NR</b>
	9.53 [3/8]	22.23 [7/8]	8/1.00	15/0.99	15/0.98	15/0.98	15/0.97	12/0.96
	12.7 [1/2]	22.23 [7/8]	8/1.00	15/0.99	15/0.98	15/0.98	15/0.97	15/0.96

**NOTES:**

- 1) Do not exceed 46 meters linear line length.
- 2) \* Do not exceed 15 meters vertical separation between indoor and outdoor units.
- 3) \*\* 19.05mm [3/4 in.] vapor line should only be used for 2 ton systems if outdoor unit is below or at same level as indoor unit to assure proper oil return.
- 4) Always use the smallest liquid line allowable to minimize refrigerant charge.
- 5) Applications shaded in light gray indicate capacity multipliers between 0.90 and 0.96 which are not recommended, but are allowed.
- 6) Applications shaded in dark gray are not recommended due to excessive liquid or suction pressure drop.

[ ] Designates Metric Conversions

## Performance Data @ AHRI Standard Conditions – Cooling

**Note:** Ratings contained in this document are subject to change. For up-to-date and expanded ratings, please visit the AHRI web site ([www.ahridirectory.org](http://www.ahridirectory.org)).

Tested Combination							
Outdoor Unit	Air Handler	Total Capacity BTU/H [kW]	Net Sensible BTU/H [kW]	Net Latent BTU/H [kW]	SEER	EER	Indoor CFM [L/s]
UA2024AJV	RHMV2421MEAC	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]
UA2036AJV	RHMV6021SEAC	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]
UA2048AJV	RHMV6021SEAC	46000 [13.5]	34400 [10.1]	11600 [3.4]	20.5	13.0	1550 [731.5]
UA2060AJV	RHMV6024MEAC	57000 [16.7]	40800 [12.0]	16200 [4.7]	20.5	13.0	1650 [778.7]

U802V: Ultra 2-Stage 80% ECM Furnace Ratings									
Outdoor Unit	Furnace	Indoor Coil	Total Capacity BTU/H [kW]	Net Sensible BTU/H [kW]	Net Latent BTU/H [kW]	SEER	EER	Indoor CFM [L/s]	
UA2024AJV	U802VA050317M	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
		RCF2421MEA	23800 [7.0]	17700 [5.2]	6100 [1.8]	20.0	14.5	825 [389.4]	
		RCF3621MEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
	U802VA075317M	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
		RCF2421MEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
		RCF3621MEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
	U802VA075317Z	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
	U802VA075421M	RCF2421MEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
		RCF3621MEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
	U802VA075421Z	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
		RCF2421MEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
		RCF3621MEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
	U802VA100521M	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
		RCF2421MEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
		RCF3621MEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
	U802VA100521Z	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
		RCF2421MEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
		RCF3621MEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]	
	UA2036AJV	U802VA050317M	RCF3621MEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	19.5	12.2	1175 [554.5]
			RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	12.5	1175 [554.5]
		U802VA075317M	RCF3621MEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.0	12.5	1225 [578.1]
			RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	12.5	1225 [578.1]
		U802VA075421M	RCF3621MEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	19.5	12.5	1225 [578.1]
			RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]
RCF6024MEA			36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]	
U802VA075421Z		RCF3621MEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	19.5	12.5	1225 [578.1]	
		RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]	
U802VA100521M		RCF3621MEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	19.5	13.0	1225 [578.1]	
		RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]	
		RCF6024MEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]	
U802VA100521Z		RCF3621MEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	19.5	12.5	1225 [578.1]	
		RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]	
U802VA125524M		RCF3621MEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	19.5	13.0	1225 [578.1]	
		RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]	
		RCF6024MEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]	
U802VA125524Z		RCF3621MEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	19.5	12.5	1225 [578.1]	
		RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]	
		RCF6024MEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]	

[ ] Designates Metric Conversions

## Performance Data @ AHRI Standard Conditions – Cooling (con't.)

**Note:** Ratings contained in this document are subject to change. For up-to-date and expanded ratings, please visit the AHRI web site ([www.ahridirectory.org](http://www.ahridirectory.org)).

U802V: Ultra 2-Stage 80% ECM Furnace Ratings								
Outdoor Unit	Furnace	Indoor Coil	Total Capacity BTU/H [kW]	Net Sensible BTU/H [kW]	Net Latent BTU/H [kW]	SEER	EER	Indoor CFM [L/s]
UA2048AJV	U802VA075421M	RCF6021SEA	45000 [13.2]	33700 [9.9]	11300 [3.3]	20.5	12.0	1550 [731.5]
		RCF6024MEA	46500 [13.6]	34800 [10.2]	11700 [3.4]	20.5	12.5	1550 [731.5]
	U802VA075421Z	RCF6021SEA	45000 [13.2]	33700 [9.9]	11300 [3.3]	20.0	12.0	1550 [731.5]
	U802VA100521M	RCF6021SEA	45500 [13.3]	34000 [10.0]	11500 [3.4]	20.5	12.5	1575 [743.3]
		RCF6024MEA	47000 [13.8]	35100 [10.3]	11900 [3.5]	20.5	13.0	1575 [743.3]
	U802VA100521Z	RCF6021SEA	45500 [13.3]	34000 [10.0]	11500 [3.4]	20.0	12.5	1550 [731.5]
	U802VA125524M	RCF6021SEA	45500 [13.3]	34000 [10.0]	11500 [3.4]	20.5	13.0	1550 [731.5]
		RCF6024MEA	47000 [13.8]	35100 [10.3]	11900 [3.5]	20.5	13.0	1550 [731.5]
UA2060AJV	U802VA075421M	RCF6021SEA	55500 [16.3]	39700 [11.6]	15800 [4.6]	17.5	11.7	1675 [790.5]
		RCF6024MEA	56000 [16.4]	40100 [11.8]	15900 [4.7]	19.5	12.0	1675 [790.5]
	U802VA075421Z	RCF6021SEA	55500 [16.3]	39700 [11.6]	15800 [4.6]	17.5	11.7	1675 [790.5]
	U802VA100521M	RCF6021SEA	56000 [16.4]	40100 [11.8]	15900 [4.7]	18.0	12.0	1675 [790.5]
		RCF6024MEA	56500 [16.6]	40400 [11.8]	16100 [4.7]	20.0	12.5	1675 [790.5]
	U802VA100521Z	RCF6021SEA	55500 [16.3]	39700 [11.6]	15800 [4.6]	17.5	12.0	1675 [790.5]
	U802VA125524M	RCF6021SEA	56000 [16.4]	40100 [11.8]	15900 [4.7]	18.0	12.5	1675 [790.5]
		RCF6024MEA	57000 [16.7]	40800 [12.0]	16200 [4.7]	20.0	12.5	1675 [790.5]

U96V: 96% AFUE 2-Stage Variable Speed Multipoise Gas Furnace Ratings								
Outdoor Unit	Furnace	Indoor Coil	Total Capacity BTU/H [kW]	Net Sensible BTU/H [kW]	Net Latent BTU/H [kW]	SEER	EER	Indoor CFM [L/s]
UA2024AJV	U96VA0402317M	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.0	825 [389.4]
		RCF2421MEA	23800 [7.0]	17700 [5.2]	6100 [1.8]	20.5	14.0	825 [389.4]
	U96VA0602317M	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.0	825 [389.4]
		RCF2421MEA	23800 [7.0]	17700 [5.2]	6100 [1.8]	20.5	14.0	825 [389.4]
	U96VA0702317M	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.5	825 [389.4]
		RCF2421MEA	23800 [7.0]	17700 [5.2]	6100 [1.8]	20.0	14.5	825 [389.4]
	U96VA0852521M	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.0	825 [389.4]
		RCF2421MEA	23800 [7.0]	17700 [5.2]	6100 [1.8]	20.0	14.0	825 [389.4]
RCF3621MEA		24000 [7.0]	17800 [5.2]	6200 [1.8]	20.0	14.0	825 [389.4]	
UA2036AJV	U96VA0602317M	RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	12.5	1200 [566.3]
	U96VA0702317M	RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.0	12.2	1200 [566.3]
	U96VA0852521M	RCF3621MEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	19.5	12.5	1225 [578.1]
		RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]
	U96VA1002521M	RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]
	U96VA1152524M	RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	12.5	1225 [578.1]
RCF6024MEA		36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	12.5	1225 [578.1]	
UA2048AJV	U96VA0602317M	RCF6021SEA	44000 [12.9]	32900 [9.6]	11100 [3.3]	20.5	12.5	1200 [566.3]
	U96VA0702317M	RCF6021SEA	43500 [12.7]	32500 [9.5]	11000 [3.2]	20.5	12.2	1200 [566.3]
	U96VA0852521M	RCF6021SEA	45000 [13.2]	33700 [9.9]	11300 [3.3]	20.5	12.0	1550 [731.5]
	U96VA1002521M	RCF6021SEA	45000 [13.2]	33700 [9.9]	11300 [3.3]	20.5	12.0	1550 [731.5]
	U96VA1152524M	RCF6021SEA	45000 [13.2]	33700 [9.9]	11300 [3.3]	20.5	12.0	1575 [743.3]
RCF6024MEA		46500 [13.6]	34800 [10.2]	11700 [3.4]	20.5	12.5	1575 [743.3]	
UA2060AJV	U96VA0852521M	RCF6021SEA	55000 [16.1]	39400 [11.5]	15600 [4.6]	17.5	12.0	1550 [731.5]
	U96VA1002521M	RCF6021SEA	55500 [16.3]	39700 [11.6]	15800 [4.6]	17.5	11.7	1675 [790.5]
	U96VA1152524M	RCF6021SEA	55500 [16.3]	39700 [11.6]	15800 [4.6]	17.5	11.7	1675 [790.5]
		RCF6024MEA	56000 [16.4]	40100 [11.8]	15900 [4.7]	19.5	12.0	1675 [790.5]

[ ] Designates Metric Conversions

## Performance Data @ AHRI Standard Conditions – Cooling (con't.)

**Note:** Ratings contained in this document are subject to change. For up-to-date and expanded ratings, please visit the AHRI web site ([www.ahridirectory.org](http://www.ahridirectory.org)).

U97V: 97% AFUE Modulating Gas Furnace Ratings								
Outdoor Unit	Furnace	Indoor Coil	Total Capacity BTU/H [kW]	Net Sensible BTU/H [kW]	Net Latent BTU/H [kW]	SEER	EER	Indoor CFM [L/s]
UA2024AJV	U97VA060M317K	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.0	825 [389.4]
		RCF2421MEA	23800 [7.0]	17700 [5.2]	6100 [1.8]	20.5	14.0	825 [389.4]
	U97VA070M317K	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.0	825 [389.4]
		RCF2421MEA	23600 [6.9]	17500 [5.1]	6100 [1.8]	20.5	14.0	775 [365.8]
	U97VA085M521K	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.0	825 [389.4]
		RCF2421MEA	23800 [7.0]	17700 [5.2]	6100 [1.8]	20.0	14.0	825 [389.4]
RCF3621MEA		24000 [7.0]	17800 [5.2]	6200 [1.8]	20.0	14.0	825 [389.4]	
UA2036AJV	U97VA060M317K	RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	12.5	1200 [566.3]
	U97VA070M317K	RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.0	12.2	1200 [566.3]
	U97VA085M521K	RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]
	U97VA100M521K	RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]
	U97VA115M524K	RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	12.5	1225 [578.1]
		RCF6024MEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	12.5	1225 [578.1]
UA2048AJV	U97VA060M317K	RCF6021SEA	44000 [12.9]	32900 [9.6]	11100 [3.3]	20.5	12.5	1200 [566.3]
	U97VA070M317K	RCF6021SEA	43500 [12.7]	32500 [9.5]	11000 [3.2]	20.5	12.2	1200 [566.3]
	U97VA085M521K	RCF6021SEA	44000 [12.9]	32900 [9.6]	11100 [3.3]	20.5	12.5	1300 [613.5]
	U97VA100M521K	RCF6021SEA	44500 [13.0]	33300 [9.8]	11200 [3.3]	20.5	12.5	1350 [637.1]
	U97VA115M524K	RCF6021SEA	44500 [13.0]	33300 [9.8]	11200 [3.3]	20.5	13.0	1350 [637.1]
		RCF6024MEA	46500 [13.6]	34800 [10.2]	11700 [3.4]	20.5	12.5	1575 [743.3]
UA2060AJV	U97VA085M521K	RCF6021SEA	55000 [16.1]	39400 [11.5]	15600 [4.6]	17.5	12.0	1550 [731.5]
	U97VA100M521K	RCF6021SEA	55000 [16.1]	39400 [11.5]	15600 [4.6]	17.5	12.0	1550 [731.5]
	U97VA115M524K	RCF6021SEA	55500 [16.3]	39700 [11.6]	15800 [4.6]	17.5	11.7	1675 [790.5]
		RCF6024MEA	56000 [16.4]	40100 [11.8]	15900 [4.7]	19.5	12.0	1675 [790.5]

U98V: 98% AFUE Modulating Upflow Gas Furnace Ratings								
Outdoor Unit	Furnace	Indoor Coil	Total Capacity BTU/H [kW]	Net Sensible BTU/H [kW]	Net Latent BTU/H [kW]	SEER	EER	Indoor CFM [L/s]
UA2024AJV	U98VA060M317U	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.0	825 [389.4]
		RCF2421MEA	23800 [7.0]	17700 [5.2]	6100 [1.8]	20.5	14.0	825 [389.4]
	U98VA070M317U	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.0	825 [389.4]
		RCF2421MEA	23600 [6.9]	17500 [5.1]	6100 [1.8]	20.5	14.0	775 [365.8]
	U98VA085M521U	RCF2417SEA	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.0	825 [389.4]
		RCF2421MEA	23800 [7.0]	17700 [5.2]	6100 [1.8]	20.0	14.0	825 [389.4]
RCF3621MEA		24000 [7.0]	17800 [5.2]	6200 [1.8]	20.0	14.0	825 [389.4]	
UA2036AJV	U98VA060M317U	RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	12.5	1200 [566.3]
	U98VA070M317U	RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.0	12.2	1200 [566.3]
	U98VA085M521U	RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]
	U98VA100M521U	RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	13.0	1225 [578.1]
	U98VA115M524U	RCF6021SEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	12.5	1225 [578.1]
		RCF6024MEA	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	12.5	1225 [578.1]
UA2048AJV	U98VA060M317U	RCF6021SEA	44000 [12.9]	32900 [9.6]	11100 [3.3]	20.5	12.5	1200 [566.3]
	U98VA070M317U	RCF6021SEA	43500 [12.7]	32500 [9.5]	11000 [3.2]	20.5	12.2	1200 [566.3]
	U98VA085M521U	RCF6021SEA	44000 [12.9]	32900 [9.6]	11100 [3.3]	20.5	12.5	1300 [613.5]
	U98VA100M521U	RCF6021SEA	44500 [13.0]	33300 [9.8]	11200 [3.3]	20.5	12.5	1350 [637.1]
	U98VA115M524U	RCF6021SEA	44500 [13.0]	33300 [9.8]	11200 [3.3]	20.5	13.0	1350 [637.1]
		RCF6024MEA	46500 [13.6]	34800 [10.2]	11700 [3.4]	20.5	12.5	1575 [743.3]
UA2060AJV	U98VA085M521U	RCF6021SEA	55000 [16.1]	39400 [11.5]	15600 [4.6]	17.5	12.0	1550 [731.5]
	U98VA100M521U	RCF6021SEA	55000 [16.1]	39400 [11.5]	15600 [4.6]	17.5	12.0	1550 [731.5]
	U98VA115M524U	RCF6021SEA	55500 [16.3]	39700 [11.6]	15800 [4.6]	17.5	11.7	1675 [790.5]
		RCF6024MEA	56000 [16.4]	40100 [11.8]	15900 [4.7]	19.5	12.0	1675 [790.5]

[ ] Designates Metric Conversions

## Performance Data @ AHRI Standard Conditions – Cooling (con't.)

**Note:** Ratings contained in this document are subject to change. For up-to-date and expanded ratings, please visit the AHRI web site ([www.ahridirectory.org](http://www.ahridirectory.org)).

Air Handler Ratings							
Outdoor Unit	Air Handler	Total Capacity BTU/H [kW]	Net Sensible BTU/H [kW]	Net Latent BTU/H [kW]	SEER	EER	Indoor CFM [L/s]
UA2024AJV	RHMV2417SEAC	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.0	825 [389.4]
UA2024AJV	RHMV2421HEAC	24000 [7.0]	17800 [5.2]	6200 [1.8]	20.5	14.0	825 [389.4]
UA2036AJV	RHMV6024MEAC	36000 [10.6]	27100 [7.9]	8900 [2.6]	20.5	12.5	1225 [578.1]
UA2048AJV	RHMV6024MEAC	47000 [13.8]	35100 [10.3]	11900 [3.5]	20.5	12.5	1675 [790.5]
UA2060AJV	RHMV6021SEAC	56000 [16.4]	40100 [11.8]	15900 [4.7]	18.0	12.5	1625 [766.9]

[ ] Designates Metric Conversions

## GUIDE SPECIFICATIONS

### General

#### System Description

Outdoor-mounted, air-cooled, split-system air conditioner composite base pan unit suitable for ground or rooftop installation. Unit consists of a hermetic compressor, an air-cooled coil, forward swept blade propeller-type condenser fan, suction and legend line service valve, and a control box. Unit will discharge supply air upward as shown on contract drawings. Unit will be used in a refrigeration circuit to match up to a coil unit.

#### Quality Assurance

- Unit will be rated in accordance with the latest edition of AHRI Standard 210.
- Unit will be certified for capacity and efficiency, and listed in the latest AHRI directory.
- Unit construction will comply with latest edition of ANSI/ASHRAE and with NEC.
- Unit will be constructed in accordance with UL standards and will carry the UL label of approval. Unit will have c-UL-us approval.
- Unit cabinet will be capable of withstanding ASTM B117 1000-hr salt spray test.
- Air-cooled condenser coils will be leak tested at 150 psig and pressure tested at 550 psig.
- Unit constructed in ISO9001 approved facility.

#### Delivery, Storage, and Handling

- Unit will be shipped as single package only and is stored and handled per unit manufacturer's recommendations.

**Warranty (for inclusion by specifying engineer)** – U.S. and Canada only.

### Products

#### Equipment

Factory assembled, single piece, air-cooled air conditioner unit. Contained within the unit enclosure is all factory wiring, piping, controls, compressor, refrigerant charge R-410A, and special features required prior to field start-up.

#### Unit Cabinet

- Unit cabinet will be constructed of galvanized steel, bonderized, and coated with a powder coat paint.
- All units constructed with louver coil protection and corner post. Louver can be removed by removing one fastener per louver panel.

### AIR-COOLED, SPLIT-SYSTEM AIR CONDITIONER

#### UA20

#### 1-1/2 TO 5 NOMINAL TONS

#### Fans

- Condenser fan will be direct-drive propeller type, discharging air upward.
- Condenser fan motors will be totally enclosed, 1-phase type with class B insulation and permanently lubricated bearings. Shafts will be corrosion resistant.
- Fan blades will be statically and dynamically balanced.
- Condenser fan openings will be equipped with coated steel wire safety guards.

#### Compressor

- Compressor will be hermetically sealed.
- Compressor will be mounted on rubber vibration isolators.
- Compressor will be covered with a sound absorbing blanket.

#### Condenser Coil

- Condenser coil will be air cooled.
- Coil will be constructed of aluminum fins mechanically bonded to copper tubes.

#### Refrigeration Components

- Refrigeration circuit components will include liquid-line shutoff valve with sweat connections, vapor-line shutoff valve with sweat connections, system charge of R-410A refrigerant, and compressor oil.
- Unit will be equipped with filter drier for R-410A refrigerant for field installation.

#### Operating Characteristics

- The capacity of the unit will meet or exceed \_\_\_\_ Btuh at a suction temperature of \_\_\_\_ °F/°C. The power consumption at full load will not exceed \_\_\_\_ kW.
- Combination of the unit and the evaporator or fan coil unit will have a total net cooling capacity of \_\_\_\_ Btuh or greater at conditions of \_\_\_\_ CFM entering air temperature at the evaporator at \_\_\_\_ °F/°C wet bulb and \_\_\_\_ °F/°C dry bulb, and air entering the unit at \_\_\_\_ °F/°C.
- The system will have a SEER of \_\_\_\_ Btuh/watt or greater at DOE conditions.

#### Electrical Requirements

- Nominal unit electrical characteristics will be \_\_\_\_ v, single phase, 60 hz. The unit will be capable of satisfactory operation within voltage limits of \_\_\_\_ v to \_\_\_\_ v.
- Nominal unit electrical characteristics will be \_\_\_\_ v, three phase, 60 hz. The unit will be capable of satisfactory operation within voltage limits of \_\_\_\_ v to \_\_\_\_ v.
- Unit electrical power will be single point connection.
- Control circuit will be 24v.

#### Special Features

- Refer to section of this literature identifying accessories and descriptions for specific features and available enhancements.
- EcoNet control with appropriate software version is required for full featured operation.

**GENERAL TERMS OF LIMITED WARRANTY\***

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.


**\*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.**

Conditional Unit Replacement  
(Registration Required) ..... Ten (10) Years  
Parts ..... Ten (10) Years









*In keeping with its policy of continuous progress and product improvement, Ruud reserves the right to make changes without notice.*

Ruud Heating, Cooling & Water Heating • P.O. Box 17010  
Fort Smith, Arkansas 72917 • [www.ruud.com](http://www.ruud.com)

Ruud Canada • 125 Edgeware Road, Unit 1  
Brampton, Ontario • L6Y 0P5

**RELY ON RUUD.™**

PRINTED IN U.S.A. 8/18 QG FORM NO. A22-224 REV. 3