

ZP14KVE-PFV

HFC, R-410A, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

Production Status: This model is obsolete and is no longer in production for both OEM and service replacement. Please contact Customer Service about possible replacement models.

Summary

Performance		
Evaporator Temp. (°F)	50.00	50
Condensing Temp. (°F)	100.00	115
Return Gas Temp. (°F)	70.00	70
Liquid Temp. (°F)	85.00	100
Capacity (BTU/hr)	20200	18200
Power (W):	958	1185
Current (Amps):	4.2	5.3
EER(BTU/Wh):	21.05	15.35
Mass Flow (lbs/hr):	246	241
Sound Data @ 50 / 115		
Sound Power (dBA):	66 Avg	71 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2021-03-03	
Mechanical		
Displacement (in^3/Rev):	.88	
Displacement (ft^3/Hr):		
Overall Length (in):	9.69	
Overall Width (in):	9.69	
Overall Height (in):	14.94	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	
Mounting Height (in):	15.70	

Suction Size (in),Type:	3 / 4 Stub
Discharge Size (in),Type:	1 / 2 Stub
Initial Oil Charge (oz):	21
Oil Recharge (oz):	17
Oil Type:	3MA
Net Weight (lbs):	44.3
Internal Free Volume (in^3):	

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA High* (Amps):	48
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	12.5
Max Operating Current (Amps):	10.00
RLA, MCC/1.4(use for contactor selection)(Amps):	8.9
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	8.0
RPM:	3500
Box IP :	21
UL File No:	SA2337- 20031216
UL File Date:	2003-12-16

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Run Capacitor	014-0064-06	30.0	0.0	370	
Start Capacitor	014-0061-27	88.0	106.0	330	

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
-------------	---------	-------	-----------	-------------

No data available in table

Nomenclature

ZP14KVE-PFV
Family Series
Z: Scroll
Application Range
P: A/C - R-410A/B
Capacity
14K: Capacity Multiplier-1000
Model Variation
V: Model Variation
Oil Type
E: Polyol Ester
Motor Type
P: 1 Phase/Capacitor Run, Permanent Split Capacitor
Motor Protection
F: Internal Inherent Protection
Voltage
V: 60Hz (208/230-1) 50Hz (-)