

ZP25K5E-PFV

HFC, R-410A, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Copeland Wholesaler. Please check with your local Copeland Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45.00	50
Condensing Temp. (°F)	130.00	100
Return Gas Temp. (°F)	65.00	70
Liquid Temp. (°F)	115.00	85
Capacity (BTU/hr)	25200	34300
Power (W):	2520	1640
Current (Amps):	11.1	7.4
EER(BTU/Wh):	10	20.9
Mass Flow (lbs/hr):	372	421
Sound Data @ 45 / 130		
Sound Power (dBA):	66 Avg	71 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2017-03-01	
Mechanical		
Displacement (in^3/Rev):	1.46	
Displacement (ft^3/Hr):		
Overall Length (in):	9.70	
Overall Width (in):	9.70	
Overall Height (in):	15.30	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

Mounting Height (in):	16.00
Suction Size (in),Type:	1 1 / 4 Rotalock
Discharge Size (in),Type:	1 Rotalock
Initial Oil Charge (oz):	25
Oil Recharge (oz):	21
Oil Type:	3MA
Net Weight (lbs):	48.4
Internal Free Volume (in^3):	124.5

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical	
LRA High* (Amps):	73
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	22
Max Operating Current (Amps):	13.80
RLA, MCC/1.4(use for contactor selection)(Amps):	15.7
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	14.1
RPM:	3500
Box IP :	21
UL File No:	SA2337-20031216
UL File Date:	2003-12-16

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors					
Type	Part No	Low MFD	High MFD	Volts	User Description
Run Capacitor	014-0064-08	40.0	0.0	370	
Start Capacitor	014-0061-27	88.0	106.0	330	

Alternate Applications				
Refrigerant	Voltage	Phase	Frequency	Application
No data available in table				

Nomenclature

ZP25K5E-PFV

Family Series

Z: Scroll

Application Range

P: A/C - R-410A/B

Capacity

25K: Capacity Multiplier-1000

Oil Type

E: Polyol Ester