

ZPS40K7E-PFV

HFC, R-410A, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Copeland Wholesaler. Please check with your local Copeland Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45.00	50
Condensing Temp. (°F)	130.00	115
Return Gas Temp. (°F)	65.00	70
Liquid Temp. (°F)	115.00	100
Capacity (BTU/hr)	42000	51300
Power (W):	3710	3070
Current (Amps):	17.3	14.5
EER(BTU/Wh):	11.3	16.7
Mass Flow (lbs/hr):	609	679
Sound Data @ 50 / 115		
Sound Power (dBA):	70 Avg	75 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2023-05-19	
Mechanical		
Displacement (in ³ /Rev):	2.37	
Displacement (ft ³ /Hr):		
Overall Length (in):	9.69	
Overall Width (in):	9.69	
Overall Height (in):	16.93	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	
Mounting Height (in):	17.70	
Suction Size (in),Type:	7 / 8 Stub	
Discharge Size (in),Type:	1 / 2 Stub	
Initial Oil Charge (oz):	42	
Oil Recharge (oz):	36	
Oil Type:	3MA	
Net Weight (lbs):	78.8	
Internal Free Volume (in ³):		

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA High* (Amps):	126.5
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	31
Max Operating Current (Amps):	26.0
RLA, MCC/1.4(use for contactor selection)(Amps):	22.1
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	19.9
RPM:	3500
Box IP :	21
UL File No:	SA2337- 20200323
UL File Date:	2020-03-23

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Run Capacitor	014-0064-07	35.0	0.0	370	
Start Capacitor	014-0061-27	88.0	106.0	330	

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-410A HFC	208/230	1	60	A/C, 67% Load Of Compressor Model

Nomenclature

ZPS40K7E-PFV

Family Series

Z: Scroll

Application Range

P: A/C - R-410A/B

Modulation

S: Two Step

S: Two Step

Capacity

40K: Capacity Multiplier-1000

Oil Type

E: Polyol Ester

Motor Type

P: 1 Phase/Capacitor Run, Permanent Split Capacitor

Motor Protection

F: Internal Inherent Protection

Voltage

V: 60Hz (208/230-1) 50Hz (-)