

ZR57K3E-TFD

HCFC, R-22, 60 Hz, 3 - Phase, 460 V , [Also Available with Variable Frequency Drives](#)

Air Conditioning

Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Copeland Wholesaler. Please check with your local Copeland Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45.00	45
Condensing Temp. (°F)	130.00	100
Return Gas Temp. (°F)	65.00	65
Liquid Temp. (°F)	115.00	85
Capacity (BTU/hr)	58500	68500
Power (W):	5000	3440
Current (Amps):	7.3	5.5
EER(BTU/Wh):	11.7	19.9
Mass Flow (lbs/hr):	860	880
Sound Data @		
Sound Power (dBA):	74 Avg	79 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2014-03-06	
Mechanical		
Displacement (in^3/Rev):	4.71	
Displacement (ft^3/Hr):		
Overall Length (in):	9.69	
Overall Width (in):	9.83	
Overall Height (in):	17.24	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

Mounting Height (in):	18.00
Suction Size (in),Type:	1 1 / 4 Rotolock
Discharge Size (in),Type:	1 Rotolock
Initial Oil Charge (oz):	66
Oil Recharge (oz):	62
Oil Type:	3MA
Net Weight (lbs):	85.0
Internal Free Volume (in^3):	257.0

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA High* (Amps):	62
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	12.8
Max Operating Current (Amps):	11.00
RLA, MCC/1.4(use for contactor selection)(Amps):	9.1
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	8.2
RPM:	3500
Box IP :	21
UL File No:	SA2337- 19930726
UL File Date:	1993-07-26

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
No data available in table					

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-22 HCFC	380/420	3	50	Air Conditioning
R-407C HFC	460	3	60	Air Conditioning
R-407C HFC	380/420	3	50	Air Conditioning

Nomenclature

ZR57K3E-TFD

Family Series
Z: Scroll
Application Range
R: A/C - R-22/407C/134a
Capacity
57K: Capacity Multiplier-1000
Oil Type
E: Polyol Ester
Motor Type
T: 3 Phase
Motor Protection
F: Internal Inherent Protection
Voltage
D: 60Hz (460-3) 50Hz (380/420-3)